

WHAT IS CLAIMED IS:

1. A liquid crystal shutter comprising:
- a liquid crystal device including a nematic liquid crystal sealed
- 5 in between a first transparent substrate and a second transparent substrate on whose inner surfaces are formed respective transparent electrodes, said liquid crystal device having a twisted angle equal to or greater than 180° ; and
- a pair of polarizing plates between which are sandwiched said
- 10 first transparent substrate and said second transparent substrate, said polarizing plates having respective absorption axes which are substantially orthogonal to each other, said absorption axes of said polarizing plates being angled within a range of $\pm 40^\circ$ to $\pm 50^\circ$ relative to a direction in which intermediate liquid crystal molecules are orientated,
- 15 said direction indicating a direction of orientation of said liquid crystal in an intermediate portion in a direction of thickness of said liquid crystal device.
2. A liquid crystal shutter comprising:
- 20 a liquid crystal device including a nematic liquid crystal sealed in between a first transparent substrate and a second transparent substrate on whose inner surfaces are formed respective transparent electrodes, said liquid crystal device having a twisted angle equal to or greater than 180° ; and
- 25 a pair of polarizing plates between which are sandwiched said

wherein

10 3. A liquid crystal shutter according to claim 1, wherein

15

a single drive term of said liquid crystal shutter is divided into a reset term during which all pixels of said liquid crystal shutter are rendered closed and a scan term during which all the pixels or predetermined pixels are rendered opened or half-opened;

the duration of said scan term being made shorter than a holding time taken for a transmittance of said liquid crystal shutter to start to lower after it has reached its maximum with no driving voltage applied to said liquid crystal shutter.

5. A liquid crystal shutter driving method according to claim 4, wherein

a positive or negative driving voltage is applied to said liquid crystal shutter during a partial period within said scan term, said driving voltage being set to 0V during a remaining period, said period during which said driving voltage is set to 0V being varied to perform a gradation display.

10 6. A liquid crystal shutter driving method according to claim 4, wherein

the voltage applied to said liquid crystal shutter in said scan term is varied from 0V to perform a gradation display.

15 7. A liquid crystal shutter driving method according to claim 4, wherein

a single driving term of said liquid crystal shutter is controlled, depending on an operating temperature, so as to be increased at a time of a low temperature but reduced at a time of a high temperature.

20

8. A method of driving a liquid crystal shutter according to claim 1, wherein

a single driving term of said liquid crystal shutter is assigned to a scan term during which all pixels or predetermined pixels of said liquid crystal shutter are rendered opened or half-opened, said scan term being

25

0000154-010000

controlled, depending on an operating temperature, so as to be lengthened at a time of a low temperature but shortened at a time of a high temperature.

- 5 9. A method of driving a liquid crystal shutter according to claim 2, wherein

a single drive term of said liquid crystal shutter is divided into a reset term during which all pixels of said liquid crystal shutter are rendered closed and a scan term during which all the pixels or
10 predetermined pixels are rendered opened or half-opened;

the duration of said scan term being made shorter than a holding time taken for a transmittance of said liquid crystal shutter to start to lower after it has reached its maximum with no driving voltage applied to said liquid crystal shutter.

15

10. A liquid crystal shutter driving method according to claim 9, wherein

a positive or negative driving voltage is applied to said liquid crystal shutter during a partial period within said scan term, said driving
20 voltage being set to 0V during a remaining period, said period during which said driving voltage is set to 0V being varied to perform a gradation display.

11. A liquid crystal shutter driving method according to claim 9,
25 wherein

00001554-010000

the voltage applied to said liquid crystal shutter in said scan term is varied from 0V to perform a gradation display.

12. A liquid crystal shutter driving method according to claim 9,
5 wherein

a single driving term of said liquid crystal shutter is controlled, depending on an operating temperature, so as to be increased at a time of a low temperature but reduced at a time of a high temperature.

- 10 13. A method of driving a liquid crystal shutter according to claim 2, wherein

a single driving term of said liquid crystal shutter is assigned to a scan term during which all pixels or predetermined pixels of said liquid crystal shutter are rendered opened or half-opened, said scan term being
15 controlled, depending on the operating temperature, so as to be lengthened at a time of a low temperature but shortened at a time of a high temperature.

14. A method of driving a liquid crystal shutter according to claim 3,
20 wherein

a single drive term of said liquid crystal shutter is divided into a reset term during which all pixels of said liquid crystal shutter are rendered closed and a scan term during which all the pixels or predetermined pixels are rendered opened or half-opened;

- 25 the duration of said scan term being made shorter than a holding

time taken for a transmittance of said liquid crystal shutter to start to lower after it has reached its maximum with no driving voltage applied to said liquid crystal shutter.

- 5 15. A liquid crystal shutter driving method according to claim 14, wherein

a positive or negative driving voltage is applied to said liquid crystal shutter during a partial period within said scan term, said driving voltage being set to 0V during a remaining period, said period during
10 which said driving voltage is set to 0V being varied to perform a gradation display.

16. A liquid crystal shutter driving method according to claim 14, wherein

15 the voltage applied to said liquid crystal shutter in said scan term is varied from 0V to perform a gradation display.

17. A liquid crystal shutter driving method according to claim 14, wherein

20 a single driving term of said liquid crystal shutter is controlled, depending on the operating temperature, so as to be increased at a time of a low temperature but reduced at a time of a high temperature.

18. A method of driving a liquid crystal shutter according to claim 3,
25 wherein

D **E** **F** **G**